

THE CLEAR 1-STEP CHOICE TO CREATE WRITABLE SURFACES



FEATURES

- **EASY TO APPLY**
SNAP! is a Clear "rolled on" Coating, and is the easiest to apply.
- **UNLIMITED DESIGN FLEXIBILITY**
Unlimited colour palette: base paint is tinted as desired.
- **NO MESS**
SNAP! is a single component with no mixing of two cans like other Dry Erase products (1 Quart= 200 sq. ft. coverage).
- **NO ODOR**
SNAP! has a low VOC with little or no odor making it suitable to be applied in occupied settings.
- **MORE FORGIVING INSTALLATION**
SNAP! does not dry out quickly like other products when applying.
- **ONE YEAR SHELF LIFE**
Unused product can go back into the can and be used for future projects.
- **DESIGNED FOR COMMERCIAL APPLICATIONS**
SNAP! has a ten-year warranty.

SNAP! DRY ERASE PAINT

TECHNICAL DATA

Item #TS-Snap-1
Single Component
Clear Coating
Dry Erase Paint

Kit Details:

200 sq ft coverage
2 roller covers
Installation Instructions
Paint Can Opener



INSTALLATION INSTRUCTIONS

Step 1

Apply a high quality FLAT Paint+Primer-In-One tinted to the desired colour. Wait 24 hours before proceeding further.

Step 2

Inspect surface for any unwanted texture. If present, lightly sand surface to ensure it is as smooth as possible. Then clean with a microfiber cloth. Stir the product well prior to use and only apply with provided Foam Roller Cover. Apply over the painted wall using a vertical up and down coating method being sure to keep wet edge at all times.

Wait 5 days for product to cure. Begin using your new Dry Erase Wall. We recommend the use of EXPO BULLET Low Odor markers and microfiber erasers. *For full detailed installation instructions, go to odysseywallcoverings.com or call your local sales representative.*

TEST RESULTS

Test	ASTM Method	Result
VOC	D3960	4 g/l
Density	D1475	9.44 lbs/Gal
Sag Resistance	D4400	<3 mils
Crack Resistance/Elongation	D522	>32%
Gloss 60 degree	D523	85-90 @ 3 mil coating
QUV/500 Hrs, UVA 340	D4587	Visual Gloss Change - Minimal Visual Colour Change - None Other Detrimental Film Effects - None DE = 40
Flammability	E-84	Flame Spread - 5 Smoke Development - 0
Flashpoint	D92	> 200 F
Scrub Resistance	D2486	> 15,000 Cycles
Washability	D3450	98.8%

Visit odysseywallcoverings.com
for Specifications, Installation Instructions and more.



ACCESSORIES

TSI - Snap Trim



TSI - Marker Tray



TSI - Cork Trim



Micro-Fiber Erasers



Expo Bold Colour Markers



Expo Spray Cleaner



EASE OF INSTALLATION

Transcribe Wallcovering installs just like Type II commercial wallcovering. Normally railroaded to avoid vertical seams in the writing surface. SNAP! is a clear coating that is rolled over any colour flat latex paint.

EASY TO MAINTAIN

Dry erase markings are removed with a soft cloth or eraser. Expo cleaner can be used for any resistant markings. Surface should be thoroughly cleaned periodically for best performance and appearance. DO NOT USE any abrasive cleaning tools or harsh solvents. Writing surface could be permanently damaged if instructions are not followed.

TEN YEAR WARRANTY

Our Dry Erase products are guaranteed for 10 years from installation date. With proper use and maintenance our product will perform for a minimum of ten years. See detailed cleaning and maintenance instructions for proper care.



Care and Maintenance

Before Writing on Dry Erase Surface

Before initial use of the writing surface the material must be cleaned with Expo Cleaner and a soft cloth, and then towel dried. Follow with clean water and a soft cloth. Use another clean towel to dry.

Markers

We recommend the use of Expo Bold Color/Original Ink markers.

Daily Cleaning

Micro-fiber erasers or cloths are recommended to remove the dry erase markings. Change or clean the eraser/cloth often to avoid leaving excessive marker residue on the surface. For cleaning marker residue build-up, use Expo brand Whiteboard Cleaner and a soft cloth. Projection Capable items have a matte/low-glare dry erase surface that requires more frequent cleaning than Writing Only/gloss material. No markings will be permanent, but it may be necessary to use Expo Cleaner to bring these Projection Capable products back to “like new” condition.

Do not use soapy water to clean the surface, as it will leave behind a film that severely interferes with erasing. This is true of any other cleaning agent that leaves a filmy residue behind.

Long Term Care

Clean the entire surface on a regular basis to insure the ultimate performance and appearance of the product over the long term.

Do not use abrasive cleaners/cleaning tools, erasers with hard plastic edges/housing or pointed writing instruments on the dry erase surface.

SNAP! is The Clear 1-Step Choice

• DRY ERASE COATING COMPARISONS

COATING	SNAP!	Other Brand I	Other Brand W	Other Brand F
SURFACE PREP	APPLY PAINT/PRIMER IN ONE TINTED TO DESIRED COLOR	PRIME KILZ LET DRY 24 HRS, APPLY 2 COATS OF SEMI GLOSS OR GLOSS PAINTS WAIT 24HRS	PRIME COAT, THEN PAINT WITH EGGSHELL OR GLOSSIER	PRIME WITH EGG SHELL PAINT WAIT 24 HRS BEFORE COATING
COATING APPLICATION	APPLY SINGLE COAT EVENLY OVER PRIMED SURFACE	1THIN COAT WAIT 5MIN, APPLY 2ND COAT, DRIES QUICKLY WORK FAST.	WHEN APPLING COATING MUST KEEP WET EDGE PAINT IN ONE DIRECTION ONLY	1ST COAT IN 70-80 SQ FT AREA. REPEAT 2ND COAT. BACK ROLL IN SAME DIRECTION
YIELD OF PRODUCTS	200 SQFT PER QUART.	100 SQFT PER QUART(2COATS)	100 SQFT PER QUART	100 SQFT PER QUART(2COATS)
POT LIFE	ONE COMPONENT UP TO 2HRS	MIX TWO COMPONENTS, LESS THAN 1HR.	MIX TWO COMPONENTS,LESS THAN1 HR.	MIX TWO COMPNONETS,3 TO 4 HRS.
VOC	LESS THAN 50 G/L	LESS THAN 125G/L	LESS THAN 50 G/L	LESS THAN 100G/L
CURE TIME	5 DAYS	7 DAYS	5 DAYS	5 DAYS
OPEN TIME TO GO BACK IN COATING	UP TO 1HR	CAN'T GO BACK IN COATING	CAN'T GO BACK IN COATING	CAN'T GO BACK IN COATING
ROLLER COVERS	FOAM (NO LINT), NO OVER LOAD	3/8" MICROFIBER	1/4" MICROFIBER	1/4" SHORT NAP
SMELL OF PRODUCTS	NO TO SLIGHT ODOR	STRONG	ODORLESS TO MILD	STRONG
UNUSED PRODUCT	UNUSED PRODUCT CAN BE USED ON ANOTHER PROJECT	NO CAN'T BE REUSED	NO CAN'T BE REUSED	NO CAN'T BE REUSED
SHELF LIFE OF PRODUCTS	1 YEAR	1 YEAR	1 YEAR	1 YEAR
SIZE OF PRODUCTS	200 SQFT QUART	100 SQFT QUART	100 SQFT QUART	100 SQFT QUART --- 400 SQFT GAL
WHAT IS PROVIDED IN A KIT	ROLLER COVER, STIR STICK, AND OPENER	2 ROLLER COVERS AND STIR STICK	COATING ONLY	ROLLER COVER AND STIR STICK
COMPONENTS	ONE	TWO MIXING REQUIRED	TWO MIXING REQUIRED	TWO MIXING REQUIRED
POST APLICATION TREATMENT	NO	NO	YES	NO
LAYOFF IN ONE DIRECTION	NO LAYOFF REQUIRED , NO MAINTAINING WET EDGE	MUST LAYOFF IN ONE DIRECTION, MUST MAINTAIN WET EDGE.	MUST LAYOFF IN ONE DIRECTION, MUST MAINTAIN WET EDGE	MUST LAYOFF IN ONE DIRECTION,MUST MAINTAIN WET EGDE.
BACK ROLL	YES CAN BACK ROLL, IF NEEDED	NO CAN'T BE BACK ROLLED	NO CAN'T BE BACKED ROLLED	NO CAN'T BE BACKED ROLLED
COATS OF PRODUCT	ONE ONLY	TWO COATS	ONE ONLY	TWO COATS
CUT IN WALLS	UP TO 1 HR BEFORE APPLING COATING	MUST CUT IN AS YOU ROLL WALL.	MUST CUT IN AS YOU ROLL WALL.	MUST CUT IN AS YOU ROLL WALL.
SHIPPING	FREEZE THAW- CAN BE SHIPPED IN COLD WEATHER, CAN BE SHIPPED BY AIR.	CAN'T BE SHIPPED IN COLD WEATHER,WILL FREEZE CAN'T USE.	CAN'T BE SHIPPED IN COLD WEATHER, WILL FREEZE CAN'T USE.	CAN'T BE SHIPPED IN COLD WEATHER, WILL FREEZE CAN'T USE.