



Katari Product Profile

Katari embraces the beauty of nature with its warm and inviting basket- weave design. Styled to capture the intricate detail of the woven fibers, the depth and dimension of the weave is further accentuated by a wash of color. Katari's palette of 25 colors mingles earth tones with accents emulating natural dyes like cumin and madder root.

Installation Notes:	Random Reversible		
Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	612 G/LM
		13.2 oz./SY	442 G/SM
	Fabric Weight	2.5 oz./LY	85 G/LM
	Vinyl Weight	27.5 oz./LY	520 G/LM
	Fabric Type	Poly Cotton Osnaburg	·
	Material Width	53 / 54"	134 / 137 cm
Fire Classification Results:	ASTM E-84 Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10 PASS rating as tested under NFPA 286 (Corner burn test) CAN/ULC S102-10 Fire Test: Class A, Flame Spread: 15; Smoke Developed: 75		
	OAN, 010 3102	——————————————————————————————————————	The opicaa. 10, official Developed. 70
Features:	Len-Tex Wallcoverings use Clean Vinyl Technology™		
	 Phthalate-free 		
	 Alumina trihydrate fire retardant (antimony-free) 		
	 Ultra-Fresh® antimicrobial (non-arsenate) 		

- No heavy metals or formaldehyde
 - Printed exclusively with water-based, low VOC AQUA CLEAR™ inks
 Roller applied AQUA-CLEAR 3 0™ top finish for improved stain
 - Roller applied AQUA-CLEAR 3.0™ top finish for improved stain resistance
 - Microventing for permeability is available on a custom order basis
 - Advanced Warning Effect (ionization-type smoke detector)
 - Five-year warranty against materials defects.
- All material components are Made in the U.S.A.

Environmental Attributes:

- Ultra-low emitting Pass rating under CA 01350
- Listed on state of California Collaborative for High Performing Schools (CHPS)
- SCS Indoor Advantage™ Gold Certified
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant
- Published Health Product Declaration (HPD) v2.1 LEED eligible

The flammability rating indicated herein has been determined under controlled laboratory conditions and is not intended to reflect hazards presented by this or any other material under actual fire conditions.

Ultra-Fresh® is a registered trademark of Thomson Research Associates Inc.











