

# Freya

## New Product Profile

Like a snapshot in time, Freya captures the memory of the wind rippling across water, creating sand dunes, and piling snow in drifts. The flowing movement of this design adds a natural yet dramatic touch to any interior project.

**Installation Notes:** Straight across match at 52"; REPEAT: 20" V x 26" H 1/2 drop

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	612 G/LM
		13.2 oz./SY	442 G/SM
	Fabric Weight	2.5 oz./LY	85 G/LM
	Vinyl Weight	27.5 oz./LY	520 G/LM
	Fabric Type	Non-Woven	
	Material Width	53 / 54"	134 / 137 cm

**Fire Classification Results:** ASTM E-84 Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10  
PASS rating as tested under NFPA 286 (Corner burn test)

- Features:** Len-Tex Wallcoverings use Clean Vinyl Technology™
- Phthalate-free
  - Alumina trihydrate fire retardant (antimony-free)
  - Ultra-Fresh® antimicrobial (non-arsenate)
  - No heavy metals or formaldehyde
    - Printed exclusively with water-based, low VOC AQUA CLEAR™ inks
    - Roller applied AQUA-CLEAR 3.0™ top finish for improved stain resistance
    - Microventing for permeability is available on a custom order basis
    - Advanced Warning Effect (ionization-type smoke detector)
    - Five-year warranty against materials defects.
  - All material components are Made in the U.S.A.

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
  - Listed on state of California Collaborative for High Performing Schools (CHPS)
  - SCS Indoor Advantage™ Gold Certified
  - NSF/ANSI 342 certified for sustainability
  - CA Prop 65 compliant
  - Published Health Product Declaration (HPD) – LEED eligible

The flammability rating indicated herein has been determined under controlled laboratory conditions and is not intended to reflect hazards presented by this or any other material under actual fire conditions.

Ultra-Fresh® is a registered trademark of Thomson Research Associates Inc.