

Acoustic ONLINE



ACOUSTICAL WALL PANEL

TECHNICAL DATA

Wood Species:
White oak

Dimension:
12.8" x 96" / 8.5 sq.ft.

Thickness:
28.6 mm

Finish:
10% U.V. varnish
(low V.O.C. water based clear sealer)
Antimicrobial protection


Fire rating: Class A
CAN/ULC-S102
FSV Flame Spread Value: 6.4
SDV Smoke Developed Value: 59.3




LAYERS

Top:
Wood veneer
with a fire treated MDF core

Bottom:
Stone wool with a MDF frame



Woodwerx




ACOUSTICAL PERFORMANCE

Frequency (Hz):	Absorption coefficient:
250	0.232
500	0.579
1000	0.784
2000	0.817

NRC:
0.60

SAA:
0.61



ENVIRONMENT

Stone wool:

Up to 29% recycled content

Wood:

Responsibly sourced in North America

PART OF OUR ZERO WASTE POLICY

Varnish:

Reused and/or recycled

Wood:

We maximize our production and product development to minimize waste. Any leftover is transformed into highly efficient clean-burning wood pellets



Acoustic Online

OdysseyWallcoverings.com



MADE IN CANADA

DUE TO THE NATURE OF THE PRODUCT'S UNIQUE ORGANIC MATERIAL, THERE MAY BE NATURAL COLOUR VARIATIONS AND GROWTH IMPERFECTIONS. THE FINAL PRODUCT MAY DIFFER FROM THE SAMPLES.