

Weight (Avg.):	33 oz/ly (746 gr/m ²)	Fire Safety:	• Class A - ASTM E84 (GRC)
Content:	Olefin Composite		• NFPA 101 Life Safety Code
Width:	52/54" (132/137 cm)		• CAN/ULC-S102
Backing:	Drill		
Installation:	Reverse hang / Random match		
Custom colors, weights and widths are available.			

Features and Benefits:

- Resistant to Impact • Scratches • Punctures • Tears • Stains • Chemicals
- Exceeds Type III durability performance standards
- High Performance heavyweight woven fabric backing

Environmental and Health:

- evo® PVC-free
- 30% Recycled Content
- Phthalate Free
- Red list compliant
- Meets Healthier Hospitals Safer Chemicals Guidance
- Health Product Declaration (HPD) Available
- Free of Antimicrobials
- Meets State of Washington Building Specification for Indoor Air Quality
- Meets California Section 01350 Indoor Air Quality Standard (Low VOC)
- Aggressive manufacturing materials recovery and reuse program
- Highly cleanable water-based inks
- Free of Halogenated flame retardants
- Prop 65 Compliant

USGBC LEED Support:

- Support USGBC LEED v4.1 Criteria
- Materials and Resources; Building Product Disclosure and Optimization (Includes Recycled Content; Construction Waste Management; HPD's)
- Indoor Environmental Quality; Low-Emitting Materials

Moisture, Mold, and Mildew:

inVinci evo® PVC-free wall protection functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of wallcovering.

Warranty:

inVinci evo® PVC-free wall protection is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, warranty, and other inVinci innovations, visit our website at invinciwallcovering.com.

VERSA®
DESIGNED SURFACES