

| Physical Properties: | Total Weight   | U.S. Units                    | Metric Units |
|----------------------|----------------|-------------------------------|--------------|
|                      |                |                               | 24.0 oz./LY  |
|                      |                | 16.0 oz./SY                   | 543 G/PSM    |
|                      | Fabric Type    | Osnaburg                      |              |
|                      | Material Width | 52/54"                        | 132/137 cm   |
|                      | Repeat         | Horizontal 27" x Vertical 18" |              |

**Federal Specifications:** DeNovo Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 20

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed exclusively with water-based, low VOC inks
- Microventing for permeability is available on a custom order basis
- Five year warranty against materials defects

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant

**Permeability, Moisture and Mold:**

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from DeNovoWall can be used to help control un-wanted moisture inside a building envelope.

**INSTALLATION NOTE**

Cibolo™ is a random match / reversible pattern