

Dhani™

de novo® WALL

Type II

---

<b>Physical Properties:</b>	<b>Total Weight</b>	<b>U.S. Units</b>	<b>Metric Units</b>
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Non-Woven	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 52" x Vertical 18"	

---

**Federal Specifications:** Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

---

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10  
Passes NFPA 286 Corner Burn Test

---

- Performance Features:**
- Phthalate-free
  - No heavy metals or formaldehyde
  - Printed with low VOC inks
  - Five year warranty against materials defects
- 

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
  - NSF/ANSI 342 certified for sustainability
- 

**Permeability, Moisture and Mold:** Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

**INSTALLATION NOTE**  
Dhani™ is a non-reversible match pattern

de novo® WALL

Copyright© 2018. All Rights Reserved  
Any copying or other use is expressly prohibited  
DeNovo Wall is a trademark.

MADE IN USA

