

Jetta™

de novo® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		28.0 oz./LY	868 G/PLM
		18.6 oz./SQ	630 G/PSM
	Fabric Type	Poly Cotton Osnaburg	
	Material Width	53/54"	134/137 cm
	Repeat	Horizontal 54" x Vertical 2-7/8"	

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 15
Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed with low VOC inks
 - Microventing for permeability is available on a custom order basis
 - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
 - NSF/ANSI 342 certified for sustainability
 - CA Prop 65 compliant

Permeability, Moisture and Mold: Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from DeNovoWall can be used to help control un-wanted moisture inside a building envelope.

INSTALLATION NOTE
Jetta™ is a reverse match pattern

de novo® WALL

Copyright© 2018. All Rights Reserved
Any copying or other use is expressly prohibited
DeNovo Wall is a trademark.

MADE IN USA

