

CANYON STRIA™

LOW VOC TYPE II

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.



FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 20

In addition, this product meets Type II CCC-W-408A through D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

ENVIRONMENT & HEALTH:

Meets California Section 01350 IAQ test requirements for wallcovering

Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives

Can contribute to LEED® MR 5.1 point for regional materials

All installations must conform to DeNovo's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from Denovo Wall can be used to help control un-wanted moisture inside a building envelope.

LIMITED WARRANTY:

5 year warranty against manufacturing defects. Additional information is available at www.denovowall.com



INSTALLATION NOTE
CANYON STRIA™ is a random match / reversible pattern

Copyright© 2014. All Rights Reserved
Any copying or other use is expressly prohibited
DeNovo Wall is a trademark.

